



from 160 to 240 HP



Ø 30 cm max

## FORESTRY MULCHER WITH FIXED TOOTH ROTOR.

A professional mulcher with fixed teeth for processing material up to 30 cm in diameter. The UMM/DT offers a compact size that makes it easy to handle while mulching, especially for difficult applications like steep slopes. This mulcher features a heavy duty frame with protection integrated for the cylinder and hydraulic link. It also features interchangeable counter-blades for easy maintenance and replacement, as well as a centralized greasing hub, push frame with ripper, and adjustable linkage for mounting to a 3 point hitch.

STANDARD EQUIPMENT	
PTO shaft with cam clutch	Cylinder protection
Gearbox with freewheel	Dual row protection chains
Transmission with belts in XPB	
Hydraulic hood	
Forged and hardened interchangeable counter-blades	
Interchangeable inner antiwear plates in Hardox®	
Adjustable skids	
Enclosed machine body	
Centralized greasing hub	
Hydraulic top link	
Z style self ranging system of the PTO drive shaft/gearbox	
Hydraulic hoses integrated in the frame	

  

OPTIONS	
Third row of interchangeable forged and hardened counter-blades	
W style self aligning device between PTO drive shaft/gearbox	
Mechanical push frame	
Hydraulic push frame	
Extra ripper for push frame	
Special skids to go underground	
Multiple tooth options	



## FEATURES

- Cylinder protection** to prevent cylinder damage
- Reinforced hood** helps to provide a finer product
- Forged and hardened interchangeable counter-blades** for the longest working life while providing a finer product
- Z style self ranging system of the PTO drive shaft/gearbox** helps keep the correct operating angle between the PTO shaft and the power take-off
- Centralized greasing hub** allows easy maintenance

## MAIN OPTIONS

- Third row of counter-blades** processes material to a finer finished product
- W style self aligning device between PTO drive shaft/gearbox** allows the mulcher to work in several angles without damaging the PTO
- Mechanical/hydraulic push frame** guides and pushes material away from carrier
- Additional ripper for push frame** helps with the positioning of standing material while mulching

MODEL	Tractor (HP)		PTO (rpm)	Working width (mm)	Total width (mm)	Weight (kg)	Max shredding diameter (mm)	No. teeth type C/3 + C/3/SS	No. teeth type I + C/3/SS
	min	max							
UMM/DT 200	160	240	1000	2070	2470	2180	300	42+2	58+2
UMM/DT 225	170	240	1000	2310	2710	2430	300	46+2	66+2
UMM/DT 250	180	240	1000	2550	2950	2500	300	52+2	74+2

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.