

# CHIPPER DH 910 SA



## DIMENSIONS

Chassis	Semi-trailer
Total weight (kg)	32000
Length (mm)	12765
Width (mm)	2500
Transport width (mm)	2500
Transport height (mm)	4000
Transport length (mm)	11115

## DRIVE

Engine type	diesel engine
Marke	Volvo TAD 1643 VE-B
Exhaust level	EUROMOT II
Motor power (kW / PS)	565 / 768
Fuel tank (l)	900
Torque (Nm)	3260 Nm at 1260 rpm

Engine type 2	Volvo TAD 1672 VE
Exhaust level	EUROMOT IV / Tier 4 final
Motor power (kW / PS)	515 / 700
Fuel tank (l)	900
Torque (Nm)	3200 Nm at 1260 rpm

## LOWER SCREENING DECK

Knives	5
Logdiameter Hardwood (mm)	680
Logdiameter Softwood (mm)	900
Infeed height (mm)	900
Infeed width (mm)	1000
Rotor Diameter (mm)	1300
Rotor Width (mm)	1060
Loading height (mm)	2092

## Applications

The precision chippers of the DH series 910 process waste wood, wood slabs, log and industrial wood as well as preshredded and stoned root timber to different sizes of wood chips. The machines can handle trunk diameters up to 900 mm temporary.



## Advantages

- Solid construction for continuous, industrial-scale operation
- Variable infeed speed
- Closed, robust chipping drum - high rotor weight of more than 3.5 t for constant rotation speed and evenly-shaped wood chips
- Custom-built rotor with 45 mm blade advance for economical production of very large wood chips (P100 / G100)
- Thrower driven directly by the rotor for efficient chipping and long distance throwing
- Chipping knives with overload protection
- Changeable screens for various sizes of wood chips
- Easy setup and maintenance